

High Quality Spatial Filter APERTURES

FITS MOST STANDARD SPATIAL FILTERS

Specifications

Substrate:

Material: 300 series stainless steel, non-magnetic

Substrate Diameter: 3/8 inch (0.375 inch) 9.53mm

Thickness: 0.0005 inch (12.7µm)

Finish: Black both sides

Mount:

Thickness: 0.1 inch

Diameter: 1 inch

Aperture Tolerance: ø.006 inch (0.1524mm)



Catalog #	Size (µm)	Tolerance	Price Ea. \$
SP-5	5.0µm	± 1µm	63.00
SP-10	10µm	± 1µm	60.00
SP-15	15µm	± 1.5µm	59.00
SP-25	25µm	± 2µm	59.00
SP-35	35µm	± 2µm	59.00
SP-50	50µm	± 3µm	59.00
SP-75	75µm	± 3µm	59.00
SP-100	100µm	± 4µm	59.00
SP-150	150µm	± 6µm	59.00
SP-200	200µm	± 6µm	59.00

SPATIAL FILTER HIGH POWER PINHOLES

Specifications

Substrate:

Material: Copper

Substrate Diameter: 3/8 inch (0.375 inch) 9.53mm

Thickness: 0.001 inch (25.4µm)

Finish: Black one side,
Gold one side

Mount:

Thickness: 0.1 inch

Diameter: 1 inch

Aperture Tolerance: ø.006 inch (0.1524mm)



Catalog #	Size (µm)	Tolerance	Price Ea. \$
SPHP-5	5.0µm	± 1µm	85.00
SPHP-10	10µm	± 1µm	85.00
SPHP-15	15µm	± 1.5µm	85.00
SPHP-50	50µm	± 3µm	80.00
SPHP-100	100µm	± 4µm	80.00
SPHP-150	150µm	± 6µm	74.00
SPHP-200	200µm	± 6µm	74.00

SPATIAL FILTERS FIXED SLITS

Specifications

Substrate:

Material: 300 series stainless steel, non-magnetic

Substrate Diameter: 3/8 inch (0.375 inch) 9.53mm

Thickness: 0.0005 inch (12.7µm)

Finish: Black both sides

Mount:

Thickness: 0.1 inch

Diameter: 1 inch

Aperture Tolerance: ø.006 inch (0.1524mm)



Catalog #	Size (µm)	Tolerance	Price Ea. \$
SS-5	5.0µm	± 1µm	75.00
SS-10	10µm	± 1µm	75.00
SS-15	15µm	± 1.5µm	75.00
SS-25	25µm	± 2µm	72.00
SS-50	50µm	± 3µm	72.00
SS-100	100µm	± 4µm	69.00
SS-200	200µm	± 4µm	69.00

We are the manufacturer