

High Quality Spatial Filter APERTURES

FITS MOST STANDARD SPATIAL FILTERS

Specifications

Substrate:

Material: 300 series stainless steel, non-magnetic

Substrate Diameter: 3/8 inch (0.375inch) 9.53mm

Thickness: 0.0005 inch (12.7μm)

Finish: Black both sides

Mount:

Thickness: 0.1 inch

Diameter: 1 inch

Positional Tolerance: ϕ .006 inch (0.1524mm)



Catalog #	Size (μm)	Tolerance	Price Ea. \$
SP-5	5.0μm	± 1μm	63.00
SP-10	10μm	± 1μm	60.00
SP-15	15μm	± 1.5μm	59.00
SP-25	25μm	± 2μm	59.00
SP-35	35μm	± 2μm	59.00
SP-50	50μm	± 3μm	59.00
SP-75	75μm	± 3μm	59.00
SP-100	100μm	± 4μm	59.00
SP-150	150μm	± 6μm	59.00
SP-200	200μm	± 6μm	59.00

SPATIAL FILTER HIGH POWER PINHOLES

Specifications

Substrate:

Material: Copper

Substrate Diameter: 3/8 inch (0.375inch) 9.53mm

Thickness: 0.001 inch (25.4μm)

Finish: Black one side,
Gold one side

Mount:

Thickness: 0.1 inch

Diameter: 1 inch

Positional Tolerance: ϕ .006 inch (0.1524mm)



Catalog #	Size (μm)	Tolerance	Price Ea. \$
SPHP-5	5.0μm	± 1μm	85.00
SPHP-10	10μm	± 1μm	85.00
SPHP-15	15μm	± 1.5μm	85.00
SPHP-50	50μm	± 3μm	80.00
SPHP-100	100μm	± 4μm	80.00
SPHP-150	150μm	± 6μm	74.00
SPHP-200	200μm	± 6μm	74.00

SPATIAL FILTERS FIXED SLITS

Specifications

Substrate:

Material: 300 series stainless steel, non-magnetic

Substrate Diameter: 3/8 inch (0.375inch) 9.53mm

Thickness: 0.0005 inch (12.7μm)

Finish: Black both sides

Mount:

Thickness: 0.1 inch

Diameter: 1 inch

Positional Tolerance: ϕ .006 inch (0.1524mm)



Catalog #	Size (μm)	Tolerance	Price Ea. \$
SS-5	5.0μm	± 1μm	75.00
SS-10	10μm	± 1μm	75.00
SS-15	15μm	± 1.5μm	75.00
SS-25	25μm	± 2μm	72.00
SS-50	50μm	± 3μm	72.00
SS-100	100μm	± 4μm	69.00
SS-200	200μm	± 4μm	69.00

We are the manufacturer